

## Global Performance

The flexible and cost effective coordinate measuring machine for the modern manufacturing plants. The Global Classic, equipped with a range of point to point probes, offers high precision, productivity, reliability and minimum maintenance. The Global classic is the moderate price solution for general purpose measurements and verification of complex dimensional features.

The standard configuration includes:

- FB-II Scanning compatible Controller
- Motorized Probe Head
- Touch Trigger Probe
- PC-DMIS CAD Software
- Installation and certification
- Training
- (1) year warranty

Most common options:

- Contact Scanning Probes
- Laser scanning sensors
- Video sensors
- Probe changers
- PC-DMIS CAD++
- Datapage R/T Statistical Software

- CAD Interfaces and Translators for CATIA, UG, PRO-E and others

GLOBAL Performance - Available in the following sizes:

Strokes

X (mm)

Y (mm)

Z (mm)

MPE according to ISO 10360-2 ( $\mu\text{m}$ )

05.05.05

500

500

500

from 1,5 + L/333

05.07.05

500

700

500

from 1,5 + L/333

07.10.07

700

1000

660

from 1,5 + L/333

09.12.08

900

1200

800

from 1,9 + L/333

09.15.08

900

1500

800

from 1,9 + L/333

09.20.08

900

2000

800

from 1,9 + L/333

12.15.10

1200

1500

1000

from 2,5 + L/333

12.22.10

1200

2200

1000

from 2,5 + L/333

12.30.10

1200

3000

1000

from 2,5 + L/333